

2 Part Polyurethane Compound and MDI

1. IDENTIFICATION OF THE PREPARATION AND THE COMPANY:



PRODUCT NAME: 2 Part Polyurethane MDI Compound
 SUPPLIER: Sicame UK Ltd
 Unit 4A, London Medway Commercial Park,
 James Swallow Way, Hoo, Rochester Kent
 ME3 9GX

+44 (0) 1322 444500



2. COMPOSITION/INFORMATION ON INGREDIENTS:

Labelled Components

Part A: Resin

INGREDIENTS	CAS No	%(w/w)	Symbol	Hazard Code
1171-102 castor oil	8001-79-4	<55%	N/A	None
1186-144 calcium carbonate	471-34-1	<65%	N/A	None
1186-143 sieve powder	1318-02-1	<3%	 Warning	H315, H317, H332, H334, H335, H373, H320, H360D
1162-140 DBTDL	77-58-7	<0.01%		
1184-203 liquid thixotropic	N/A	<0.5%		
			 Danger	

Part B: Hardener

INGREDIENTS	CAS No	%(w/w)	Symbol	Hazard Code
4,4 Diphenylmethane Diisocyanate Isomers and homologues	009016-87-9	100%	 Warning	H315, H317, H332, H334, H335, H373, H320, H351
			 danger	

3. HAZARDS IDENTIFICATION:

Main Health Hazards Harmful By inhalation
 Irritating to eyes, respiratory system and skin
 May cause sensitisation by inhalation

4. FIRST AID MEASURES:

INHALATION: Remove to fresh air, keep calm and if recovery is not rapid, seek medical attention

SKIN CONTACT: Remove contaminated clothing and wash with plenty of soap and water. Do not use organic solvents

EYE CONTACT: Immediate and continual flushing of the eye is essential, Seek Medical attention

INGESTION: If large amounts are ingested wash out mouth with clean cold water and seek medical attention.

5. FIRE FIGHTING MEASURES:

SUITABLE EXTINGUISHING
MEDIA:

CO₂, Water Spray, Foam or Dry Powder.

HAZARDS

Combustion Products include water; oxides of carbon and nitrogen, traces of hydrogen cyanide may also be evolved.

REQUIRE SPECIAL PROTECTIVE EQUIPMENT

FOR FIRE FIGHTERS:

In enclosed spaces wear self-contained breathing apparatus and full protective clothing

6. ACCIDENTAL RELEASE MEASURES:

PERSONAL PRECAUTIONS:

Do not breathe vapour, avoid ignition sources, and avoid contact with skin, eyes or clothing.

ENVIRONMENTAL
PRECAUTIONS:

Prevent contamination of soil, drains and surface water.

WORKPLACE
PRECAUTIONS

Ensure personnel are wearing suitable protective equipment.

METHOD OF CLEANING:

Absorb into damp sand or equivalent and place in suitable closed container for disposal in accordance with local and national regulations

7. HANDLING AND STORAGE:

7.1 HANDLING:

Wear plastic gloves if skin irritation occurs

7.2 STORAGE:

Recommended storage temperature between +10 deg. C and +25deg. C.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION:

No special precautions are necessary, although sensible industrial clothing is recommended.

EXPOSURE CONTROL LIMITS: Isocyanate 0.02 mg.m⁻³ 8 hour TWA

RESPIRATORY PROTECTION: None required.

HAND PROTECTION:

Wear plastic gloves

EYE PROTECTION:

Wear safety glasses

SKIN PROTECTION:

Wear sensible industrial clothing, wash regularly.

9. PHYSICAL AND CHEMICAL PROPERTIES:

	BASE	HARDENER
APPEARANCE:	Buff Liquid	Brown Liquid
ODOUR:	Typical of a natural vegetable oil Musty	
pH:	Not applicable	Not applicable
BOILING POINT RANGE:	Above 300 deg. C	Above 200 deg.C
MELTING POINT RANGE:	Not applicable	Not applicable
FLASH POINT:	Above 200 deg. C (open cup)	above 220 deg. C (open cup)
FLAMMABILITY:	Not flammable at normal temperatures	not flammable at normal temperatures
AUTO-FLAMMABILITY:	May auto-ignite above 300 deg C	may auto-ignite over 300 deg C
EXPLOSIVE PROPERTIES:	Not applicable	Not applicable
OXIDISING PROPERTIES:	Not applicable	Not applicable
VAPOUR PRESSURE:	<10 mbar @20C	<0.00001 mbar @20C
RELATIVE DENSITY:	1.4	1.22
SOLUBILITY IN Water:	Insoluble	Insoluble
OTHER:	Partially soluble in hydrocarbon solvents.	

10. STABILITY AND REACTIVITY:

CONDITIONS TO AVOID:	None
MATERIALS TO AVOID:	Strong alkalis and acids
HAZARDOUS DECOMPOSITION PRODUCT (S):	None when stored and used correctly. At temperatures in excess of 200 C decomposition products may include oxides of nitrogen and carbon.

11. TOXICOLOGICAL INFORMATION:

	Base	Hardener
EYE CONTACT:	Possible Irritation	Irritation
SKIN EFFECT:	Possible irritation	Possible irritation and sensitisation
INHALATION:	Irritation unlikely	Possible irritation and sensitisation
INGESTION:	Possible Purgative	Possible gastric Irritation
EXPOSURE LIMITS		0.02 mg per cubic metre, 8 hr TWA 0.07 mg per cubic metre, 15 min STEL

12. ECOLOGICAL INFORMATION:

Do not allow liquid components to escape into soil watercourses or drains

13. DISPOSAL CONSIDERATIONS:

Disposal should be in accordance with local, state or national legislation.

14. TRANSPORT INFORMATION:

Not classified as dangerous for transport

15. OTHER INFORMATION:

Date of preparation September

Liability: such information is to the best of SICAME UK subsidiary's knowledge and belief accurate and reliable as of the date indicated. However, no representation, warranty or guarantee is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy itself as to its suitability and completeness of such information for their own particular use.

The data contained in this safety data sheet has been supplied as required by the **Chemicals (Hazard Identification and Packaging for Supply) Regulations 1994** for the purpose of protecting health and safety of industrial and commercial users who are deemed capable of understanding and acting on the information provided.

Please ensure that it is passed unto the appropriate person(s) in your company, who are capable of acting on the information.